



LabService
Providers

LABORATORY EQUIPMENT & INSTRUMENTATION
PRODUCT CATALOGUE

FRIDGES & FREEZERS

FRIDGES & FREEZERS



Biostorage you can depend on

BIOPLUS 500 FRIDGE / FREEZER

- Available in 4 cabinet sizes (26 to 430 litres).
- Table top models are stackable and can be wall mounted.
- Largest model is freestanding with adjustable feet.
- Constructed of electrolytically galvanized steel sheets, coated with a grey epoxy polyester paint. Stainless steel interior housing and shelves.
- Automatic safety thermostat.
- LCD text display.
- Automatic air valve setting.
- Touch button operation.
- Real-time software program – two temperatures.
- Extended temperature range to 250°C.
- PID temperature controller.
- Connects to external alarm system.
- USB outlet.
- 10-speed fan.
- Low energy consumption.

BIOMIDI 425 FRIDGE / FREEZER

- Cost effective, ergonomically designed 425 litre storage space.
- High capacity refrigeration system designed to flexibly meet the majority of bio-material refrigeration and freezer requirements.
- Available as a refrigerator RR (-2°C to +20°C) or freezer RF (-25°C to -5°C).
- White lacquered steel or stainless-steel construction.
- 600 x 731 x 1979/2000 mm.
- Weight 112 kg.
- Modules for shelves (25) and drawers (12).
- Vacuum insulated panel technology and safe closing system.
- Insulated inner doors.
- 1 access port (24.5 mm).
- Acoustic and visual high/low temperature alarms and door alarm.
- Low noise level and low power consumption.
- Full range of accessories and fittings available.

BIOCOMPACT II 610 FRIDGE / FREEZER

- Compact, highly reliable refrigerator / freezer for the stable storage of biomaterial.
- 695 x 868 x 1875/2075 mm.
- Versatile interior configuration and a selection of fixtures and fittings to meet a wide range of storage needs.
- Available as a refrigerator RR (+2°C to +20°C) or freezer RF (-25°C to -5°C).
- Features a top mounted compressor, high performance refrigeration system, finned tube evaporator and forced air distribution.
- White lacquered steel or stainless-steel exterior.
- ABS interior with stainless steel wall rails for mounting fittings.
- Automatic re-evaporation of defrost water.
- Gross volume 583 litres.
- Weight 114 kg.
- Modules for shelves (24) and drawers (12).
- Vacuum insulated panel technology and safe closing system.
- Insulated inner doors.
- 1 access port (24.5 mm).
- Acoustic and visual high/low temperature alarms and door alarm.
- Low noise level and low power consumption.
- Internal / external ATEX compliance.
- Full range of accessories and fittings available.





Biostorage you can depend on



BIOBLOOD 500 FRIDGE / FREEZER

- Designed to meet the controlled storage requirements of blood, plasma and blood related products.
- Available as blood refrigerator (BR) +2°C/+6°C, Blood freezer (BF) -25°C/-5°C, and Plasma freezer (PF) -35°C/-5°C (PF 600/660W) and -40°C/-5°C (PF 425).
- Easy view of contents.
- 600 x 806 x 2025/2275 mm.
- White lacquered steel or stainless-steel exterior.
- Automatic re-evaporation of defrost water.
- Gross volume 500 litres.
- Weight 130 kg.
- Modules for shelves (52) and drawers (13).
- Vacuum insulated panel technology and safe closing system.
- Insulated inner doors.
- 1 access port (24.5 mm).
- Acoustic and visual high/low temperature alarms and door alarm.
- Low noise level and low power consumption.
- Full range of accessories and fittings available.

BIOULTRA UL 570 FREEZER

- Durable, long-life, ultra-low temperature cabinet with powerful, bottom mounted, cascade refrigeration system.
- White lacquered steel or stainless-steel construction.
- 856 x 979 x 1986/1996 mm.
- Weight 115 kg.
- Gross volume 570 litres.
- Consistent temperatures throughout the storage space and rapid temperature recovery on door opening.
- Vacuum insulated panel technology and safe closing system.
- Insulated inner doors.
- Temperature range -60°C to -86°C.
- 2 access ports (24.5 mm each).
- Low noise level and low power consumption.
- Full range of accessories and fittings available.



ULT U100 -86°C UPRIGHT FREEZER

- Under table, upright freezer.
- Optimal footprint for ease of installation.
- 830 x 595 x 630 mm. Net volume 91 Litres.
- Temperature range -60°C to -86°C.
- Audio and visual alarms.
- Contact for remote alarm. High / low temperature alarm.
- Digital controller with display.
- Porthole for external probe and CO2 backup.
- Prepared for external logging equipment.
- Galvanised, precoated steel outer with stainless-steel inner.
- 2 adjustable stainless-steel shelves.
- Automatic door vacuum release.
- Low cost of ownership.
- Limited maintenance and on-site service.
- Efficient cyclopentane insulation.
- Eco-friendly, NCFC-free Nature R refrigerant.
- ISO 9001, 14001 & 18001 OHSAS Certified.

ULT U250 -86°C UPRIGHT FREEZER

- Optimal footprint for ease of installation.
- 1,420 x 435 x 370 mm.
- Net weight 122 kg.
- Net volume 221 Litres.
- Temperature range -60°C to -86°C.
- Audio and visual alarms.
- Contact for remote alarm.
- High / low temperature alarm.
- Digital controller with display.
- Porthole for external probe and CO2 backup.
- Prepared for external logging equipment.
- 4 castors with brakes for ease of movement.
- Galvanised, precoated steel outer with stainless-steel inner.
- 5 adjustable stainless-steel shelves.
- Automatic door vacuum release.
- Low cost of ownership.
- Limited maintenance and on-site service.
- Dual cooling single stage compressor system.
- Efficient cyclopentane insulation.
- Eco-friendly, NCFC-free Nature R refrigerant.
- ISO 9001, 14001 & 18001 OHSAS Certified.

LT U250 -45°C UPRIGHT FREEZER

- Optimal footprint for ease of installation.
- 2,055 x 600 x 630 mm.
- Net weight 115 kg.
- Net volume 236 Litres.
- Temperature range -10°C to -45°C.
- High / low temperature alarm.
- Contact for remote alarm.
- Digital controller with display.
- Porthole for external probe and CO2 backup.
- Prepared for external logging equipment.
- 4 castors with brakes for ease of movement.
- Galvanised, precoated steel outer with stainless-steel inner.
- 5 adjustable stainless-steel shelves.
- Automatic door vacuum release.
- Low cost of ownership.
- Limited maintenance and on-site service.
- Efficient cyclopentane insulation.
- Eco-friendly, NCFC-free Nature R refrigerant.
- ISO 9001, 14001 & 18001 OHSAS Certified.



ULT C200 -86°C CHEST FREEZER

- Personal freezer for easy access and daily use in laboratories, hospitals etc. for storage of sensitive samples.
- Stable, reliable and durable with low power consumption.
- Optimal footprint for ease of installation and movement.
- 890 x 920 x 630 mm.
- Net weight 65 kg.
- Net volume 189 Litres.
- Temperature range -60°C to -86°C.
- Audio and visual alarms.
- Contact for remote alarm.
- High / low temperature alarm.
- Digital controller with display.
- Porthole for external probe and CO2 backup.
- 4 castors with brakes for ease of movement.
- Galvanised, precoated steel outer with stainless-steel inner.
- Low cost of ownership with limited maintenance and on-site service.
- Dual cooling single stage compressor system.
- Efficient cyclopentane insulation.
- Eco-friendly, NCFC-free Nature R refrigerant.
- ISO 9001, 14001 & 18001 OHSAS Certified.





**LabService
Providers**

**Equipment & instrumentation for
a wide range of laboratory environments.**

E: sales@labserviceproviders.ie

T: 021 2355450 **SALES:** 087 0669949 **SERVICE:** 086 8196737

Hérons Wood, Carrigaline, Co. Cork, Ireland.

www.labserviceproviders.ie



QUALITY
ISO 9001:2015
NSAI Certified